

Earth Bond TACKIFIER

EARTH BOND tackifier is a unique blend of synthetic organic polyacrylamides. It is the result of years of research and development. EARTH BOND is a highly concentrated tackifier that meets or exceeds all requirements for non-asphaltic emulsions for hay/straw binding. EARTH BOND is designed to create a highly viscous slurry. This aids in pumping and greatly reduces those time-consuming clogs. No cure time is needed because EARTH BOND is effective immediately. EARTH BOND also contains our own SLOW-RELEASE component to last longer than others. This whole process greatly reduces erosion of soil, mulch, seed, and fertilizer by wind or rain.

Application Rates

- 3lbs EARTH BOND treats one acre under most conditions.
- When binding hay/straw, we recommend adding 200lbs of paper mulch per acre.
- Under the most severe conditions it may be necessary to double the normal application rate to 6lbs per acre.

Physical Properties

Appearance:	White Granular Solid
Solubility:	Limited by Viscosity
Bulk Density:	40-50lbs cu/ft
Odor:	Mild
Hazardous Components:	None
Chronic Health Effects:	None

EARTH BOND contains no toxic chemicals or harmful substances.

Mixing Procedures:

- Fill tank with water and all other slurry ingredients.
- Set agitation speed to at least ½ speed.
- SLOWLY sift EARTH BOND into slurry.
Set to full speed and agitate for 3 to 5 minutes.

Packaging:

- 55 lb. multi poly lined paper bags
 - 40 bags per pallet



Turf Guard Mfg, Inc

860 West Main St
Dover-Foxcroft, ME04426
(207) 717-7078